



V 20



V 20

For ~90° corners with cold formed sheet piles, **cold-formed sheet piles to Larsen U/Z/AZ** (as interlocks vary, specific swivel range is not stated, but some swivel should be expected)

Installation

1. Please review the proper interlocking examples that are listed.
2. Thread the connector into the interlock while the sheet pile is out of the ground.
3. Adjust the connector to the appropriate position.
4. Tack or spot-weld the connector in place. Typically, a ~250mm (~10") weld, attaching the connector to the sheet pile to the top is sufficient.
5. Drive/extract the sheet pile (with the connector attached) as you would normally.

Properties

Steel grade:	S355GP, S430GP
	ASTM A572 Gr. 50/60
	ASTM A690 MARINER™ Steel
Weight:	~8.85 lb/ft



V 20

Caractéristiques

Nuances d'acier:	S355GP, S430GP
	ASTM A572 Gr. 50/60
	ASTM A690 MARINER™ Steel
Poids:	~13,2 kg/m



V 20

Anwendungen:

1. 90° Eckverbindung (durch die verschiedenen Kombinationen variieren die Schwenkbereiche in Abhängigkeit von der Schlossausbildung, vgl. V20 Larsen)
2. Übergangsprofil zwischen Leichtprofilen und AZ wie auch Larsen U- bzw. Z- Bohlen



Eigenschaften

Stahlgüten:	S355GP, S430GP
	ASTM A572 Gr. 50/60
	ASTM A690 MARINER™ Steel
Gewicht:	~13,2 kg/m



V 20

Caratteristiche

Qualità dell'acciaio:	S355GP, S430GP
	ASTM A572 Gr. 50/60
	ASTM A690 MARINER™ Steel
Peso:	~13,2 kg/m



V 20

Propiedades

Calidades de acero:	S355GP, S430GP
	ASTM A572 Gr. 50/60
	ASTM A690 MARINER™ Steel
Peso:	~13,2 kg/m

